



FILTRIFIC RAINWATER FILTER

Advanced Rainwater Filtration for Rainwater Harvesting Systems





BUILT-IN



BUILT-IN PRE-FILTRATION



LARGE PUMP CHAMBERS



EXPANDABLE RESERVOIR

CHARACTERISTICS AND ADVANTAGES

FILTRIFIC

Filtration for Storage

In order to keep the rainwater cistern or large storage tank free of debris, it is important that any rainwater captured is pre-filtered. The Filtrific Rainwater Filter pre-filters the debris from the rainwater in preparation for storage or use in rainwater irrigation system. Large & easy to access filter baskets are available in a variety of different mesh sizes wich can be customized to best suit your debris type and size.

Filtration for Irrigation

If you are planning to reusing the stored water for rainwater irrigation, the Filtrific Rainwater Filter provides up to 150 mesh (100) micron filtration which is adequate for both spray and drip irrigation.

Filtration + Built-In Pump Chamber

Aside from providing rainwater filtration, the Filtrific Rainwater Filter features a large pump chamber which transports the rainwater to an above ground storage tank.

Access Cap

Provies easy access to the filters without removing the tank lid

Filter Basket

The stainless steel filter features a detachable filter screen and is available in fourdifferent mesh

Bolt Down Lid

The two piece lid system allows the Filter Baskets to be removed without removing the whole

Filter Carriage

Supports the Filter Basket and is access to the pumping chamber

Filter Tank

The heavy-duty polyethylene tank provides multiple ports for easy connection of pumps and



RW40 SERIES RAIN WATER FILTERS


Small in size, but big in performance. The RW40 Rainwater Filter provides all the installation conveniences and advantages as the larger Rainwater Filters, but in a more compact size. With capabilities flow of up to 20 GPM (2,400 GPH), the RW40 is the perfect fit for incorporating reliable debris pre-filtration into rainwater catchment systems with moderate flow rates.

Features

- · Weight: 45 lbs
- A 4" rainwater intake port handles flow rates up to 40 GPM (2,400 GPH)
- · Interchangeable Stainless Steel Filter
- · Large pumping chamber
- · Bolt down integrated lid system

- Convenient filter access
- Removable Filter Carriage
- Front & back discharge ports for up to two pumps
- Exit Port for gravity fed systems (no pump)
- · Auxiliary Port for custom components











RW 40-24

RW75-15024

RW390-15024





